

## LATAPOXY 210 Grout



### Sigillante Epossidico Modificato

#### PRODUCT DESCRIPTION

LATAPOXY 210 Epoxy Grout is a modified emulsion tri-component grout for the installation and grouting of ceramic tile, stone and marble on most sound and clean surfaces. As adhesive for high resistance floors subject to heavy traffic.

#### USES

- For installation of ceramic tile, gres, klinker, cotto, ceramic and glass mosaic, marble, etc.
- Grouting of residential and commercial floors

#### ADVANTAGES

- High bond strength
- Easy to use and water cleanable
- Mild chemical resistance
- Water base and solvent free
- Non flammable and no unpleasant odors



### TECHNICAL DATA AT 23°C e 50% U.R.\*

LATICRETE 73/211	
Conforms to American Standard ANSI A118.8	
Powder:	grey
Resin:	white
Color:	grey
Density of mixed product:	(1.70-1.809) kg/lt
Foot traffic:	24 hours
Application Temperature:	from +5°C to +35°C

STANDARD	TEST	PERFORMANCE	
		RESULT	REQUIREMENT
ANSI A118.8 5.1	Cleanable with water	≥ 40 min.	≥ 40 min.
ANSI A118.8 5.4.2	Quarry tile share strength	1.7-2.1 MPa	2.1 MPa
ANSI A118.8 5.8	Compressive strength	21.4-24 MPa	18.3 MPa
ANSI A118.8 5.9	Tensile strength	2.4-2.75 MPa	2.1 MPa
ANSI A118.8 5.10	Flexural strength	5.5-5.9 MPa	5.0 MPa

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.